



Medium

## ARMOUR 02

Mid-cut allround tactical boot

Upper	Waterproof Leather
Lining	Sympatex Membrane
Footbed	SJ foam footbed
Outsole	Phylon/Rubber
Safety standard	O2 / HI, CI, FO, HRO, SRC, WR
Size range	EU 36-48 / UK 3.5-13.0 US 4.0-13.5 / CM 24.0-31.5
Sample weight	0.590 kg
Norms	EN ISO 20347:2012 ASTM F2892:2018



BLK



### Oil & fuel resistant

The outsole is resistant against oil and fuel.



### Heat resistant outsole (HRO)

The outsole resists high temperatures up to 300°C.



### Waterproof (WR)

Waterproof footwear prevents liquids to enter into the shoe.



### Sympatex® lining

Keeps your feet dry and comfortable in all weather conditions.



### Antistatic

Antistatic footwear prevents build-up of static electrical charges and ensures that they are discharged effectively. Volume resistance between 100 KiloOhm and 1 GigaOhm

**Industries:**

Tactical, Uniform

**Environments:**

Muddy environment, Uneven surfaces, Wet environment

**Maintenance instructions:**

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

	Description	Measure unit	Result	EN ISO 20347
<b>Upper</b>	<b>Waterproof Leather</b>			
	Upper: permeability to water vapor	mg/cm <sup>2</sup> /h	4.2	≥ 0.8
	Upper: water vapor coefficient	mg/cm <sup>2</sup>	39	≥ 15
<b>Lining</b>	<b>Sympatex Membrane</b>			
	Lining: permeability to water vapor	mg/cm <sup>2</sup> /h	3.4	≥ 2
	Lining: water vapor coefficient	mg/cm <sup>2</sup>	27	≥ 20
<b>Footbed</b>	<b>SJ foam footbed</b>			
	Footbed: abrasion resistance	cycles	400	≥ 400
<b>Outsole</b>	<b>Phylon/Rubber</b>			
	Outsole abrasion resistance (volume loss)	mm <sup>3</sup>	68	≤ 150
	Outsole slip resistance SRA: heel	friction	0.33	≥ 0.28
	Outsole slip resistance SRA: flat	friction	0.35	≥ 0.32
	Outsole slip resistance SRB: heel	friction	0.13	≥ 0.13
	Outsole slip resistance SRB: flat	friction	0.19	≥ 0.18
	Antistatic value	MegaOhm	163.9	0.1 - 1000
	ESD value	MegaOhm	NA	0.1 - 100
	Heel energy absorption	J	34	≥ 20

Sample size: 42

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and maynot be used or reproduced in any format, without written consent from us.